

The **Presco-Switch** is a Dual-Seal pressure-responsive device that opens or closes one or more integral electrical switches at predetermined setpoints in order to start or stop pump motors for pump jacks and electric submersible pump systems, stop gas engines, control valve operations and shutdown wellhead and flowline pressure.

Presco-Switch Features:

- Convenient microswitch adjustments make field setting easy
- Versatile switching arrangements satisfy most applications
- Switch housings explosion-proof design is CSA approved for Class 1 Div.1 Group D hazardous locations
- Dual-Seal design is certified to meet ANSI/ISA-12.27.01-2003 requirement for process sealing between electrical systems and combustible process fluids. Comes with weep holes for primary seal indication.



Presco has an internally adjustable set point and offers both fixed and variable differential switches available in automatic and manual reset. It is also available with a **dual microswitch, eliminating the need for two switches**. The Canadian-made product can also be easily re-built, repaired and modified to different spring ranges, while offering a larger selection than competitors.

Repeatability	1% to 2% of adjustable range
Service	Standard and H ₂ S NACE MR0175 on Select Models
Electrical Temperature Rating	-58°F to 180°F (-50°C to 82°)
Electrical Rating	5A - 125/250/480 VAC; 0.5A - 125VDC; 0.25A - 250VDC
Electrical Classification	CSA c/us approved per C22.2/UL1203/UL508; Class 1, Group D Hazardous Locations; Dual Seal Compliant per ANSI/ISA-12.27.01 requirements
Electrical Housing	Cast Aluminum; 3-1/2" OD
Electrical Connection	1/2"-14 NPT (female)
Pressure Connection	2" NPT (male); Zinc Electroplated High Strength Carbon Steel
Pressure Rating (ASME B31-3)	Type D: 3,000psig (20,684kPag); -58°F to 180°F (-50°C to 82°C) Type S: 5,000psig (34,474kPag); -58°F to 180°F (-50°C to 82°C)
Canadian Registration Number	0F20302.2
Quality Program	AQP-5164



For our sales catalogue showing available models, or for installation, operation and maintenance procedures, please visit Pem-Controls.com or contact us at sales@pem-controls.com

We understand you have a choice where you send your business.

When you choose Pembina Controls and our manufacturing partners, our goal is to ensure you are so impressed with our products and service, that you are confident in recommending us to you colleagues, clients and friends.

***DISTRIBUTION CENTRE,
ORDER DESK &
CUSTOMER SERVICE***

WWW.PEM-CONTROLS.COM



9511 - 28 Avenue, Edmonton, AB T6N 0A3



1.877.736.2462 Tel: 780.432.6821 Fax: 780.432.6867



sales@pem-controls.com



Follow us on LinkedIn for tech updates and promotions!

